

Java Programming AP Edition

U3C7 1-D Array

ARRAY BASICS


ERIC Y. CHOU, PH.D.

IEEE SENIOR MEMBER



Introducing Arrays

Array is a data structure that represents a collection of the same types of data.





Declaring Array Variables

- datatype[] arrayRefVar;

Example:

```
double[] myList;
```

- datatype arrayRefVar[]; // This style is allowed, but not preferred

Example:

```
double myList[];
```



Creating Arrays

```
arrayRefVar = new datatype[arraySize];
```

Example:

```
myList = new double[10];
```

myList[0] references the first element in the array.

myList[9] references the last element in the array.



Declaring and Creating in One Step

- datatype[] arrayRefVar = new datatype[arraySize];
`double[] myList = new double[10];`
- datatype arrayRefVar[] = new datatype[arraySize];
`double myList[] = new double[10];`



The Length of an Array

Once an array is created, its size is fixed. It cannot be changed. You can find its size using

`arrayRefVar.length`

For example,

`myList.length` returns 10



Default Values

When an array is created, its elements are assigned the default value of

0 for the numeric primitive data types, '\u0000' for char types, and false for boolean types.



Indexed Variables

The array elements are accessed through the index. The array indices are *0-based*, i.e., it starts from 0 to `arrayRefVar.length-1`. In the example in Figure 6.1, `myList` holds ten double values and the indices are from 0 to 9.

Each element in the array is represented using the following syntax, known as an *indexed variable*:

```
arrayRefVar[index];
```



Using Indexed Variables

After an array is created, an indexed variable can be used in the same way as a regular variable. For example, the following code adds the value in myList[0] and myList[1] to myList[2].

```
myList[2] = myList[0] + myList[1];
```



Array Initializers

- Declaring, creating, initializing in one step:

```
double[] myList = {1.9, 2.9, 3.4, 3.5};
```

This shorthand syntax must be in one statement.

myList = {2.9, 3.9, 4.4, 4.5}; // Compilation Error.



Declaring, creating, initializing Using the Shorthand Notation

```
double[] myList = {1.9, 2.9, 3.4, 3.5};
```

This shorthand notation is equivalent to the following statements:

```
double[] myList = new double[4];
```

```
myList[0] = 1.9;
```

```
myList[1] = 2.9;
```

```
myList[2] = 3.4;
```

```
myList[3] = 3.5;
```



CAUTION

Using the shorthand notation, you have to declare, create, and initialize the array all in one statement. Splitting it would cause a syntax error. For example, the following is wrong:

```
double[] myList;
```

```
myList = {1.9, 2.9, 3.4, 3.5};
```



Trace Program with Arrays

Declare array variable values, create an array, and assign its reference to values

```
public class Test {  
    public static void main(String[] args) {  
        int[] values = new int[5];  
        for (int i = 1; i < 5; i++) {  
            values[i] = i + values[i-1];  
        }  
        values[0] = values[1] + values[4];  
    }  
}
```

After the array is created

0	0
1	0
2	0
3	0
4	0



Trace Program with Arrays

i becomes 1

```
public class Test {  
    public static void main(String[] args) {  
        int[] values = new int[5];  
        for (int i = 1; i < 5; i++) {  
            values[i] = i + values[i-1];  
        }  
        values[0] = values[1] + values[4];  
    }  
}
```

After the array is created

0	0
1	0
2	0
3	0
4	0



Trace Program with Arrays

i (=1) is less than 5

```
public class Test {  
    public static void main(String[] args) {  
        int[] values = new int[5];  
        for (int i = 1; i < 5; i++) {  
            values[i] = i + values[i-1];  
        }  
        values[0] = values[1] + values[4];  
    }  
}
```

After the array is created

0	0
1	0
2	0
3	0
4	0



Trace Program with Arrays

After this line is executed, value[1] is 1

```
public class Test {  
    public static void main(String[] args) {  
        int[] values = new int[5];  
        for (int i = 1; i < 5; i++) {  
            values[i] = i + values[i-1];  
        }  
        values[0] = values[1] + values[4];  
    }  
}
```

After the first iteration

0	0
1	1
2	0
3	0
4	0



Trace Program with Arrays

After `i++`, `i` becomes 2

```
public class Test {  
    public static void main(String[] args) {  
        int[] values = new int[5];  
        for (int i = 1; i < 5; i++) {  
            values[i] = i + values[i-1];  
        }  
        values[0] = values[1] + values[4];  
    }  
}
```

After the first iteration

0	0
1	1
2	0
3	0
4	0



Trace Program with Arrays

```
public class Test {  
    public static void main(String[]  
        args) {  
        int[] values = new int[5],  
        for (int i = 1; i < 5; i++) {  
            values[i] = i + values[i-1];  
        }  
        values[0] = values[1] +  
            values[4];  
    }  
}
```

i (= 2) is less than 5

After the first iteration

0	0
1	1
2	0
3	0
4	0



Trace Program with Arrays

After this line is executed,
values[2] is 3 ($2 + 1$)

```
public class Test {  
    public static void main(String[] args) {  
        int[] values = new int[5];  
        for (int i = 1; i < 5; i++) {  
            values[i] = i + values[i-1];  
        }  
        values[0] = values[1] + values[4];  
    }  
}
```

After the second iteration

0	0
1	1
2	3
3	0
4	0



Trace Program with Arrays

After this, i becomes 3.

```
public class Test {  
    public static void main(String[] args) {  
        int[] values = new int[5];  
        for (int i = 1; i < 5; i++) {  
            values[i] = i + values[i-1];  
        }  
        values[0] = values[1] + values[4];  
    }  
}
```

After the second iteration

0	0
1	1
2	3
3	0
4	0



Trace Program with Arrays

i (=3) is still less than 5.

```
public class Test {  
    public static void main(String[] args) {  
        int[] values = new int[5];  
        for (int i = 1; i < 5; i++) {  
            values[i] = i + values[i-1];  
        }  
        values[0] = values[1] + values[4];  
    }  
}
```

After the second iteration

0	0
1	1
2	3
3	0
4	0



Trace Program with Arrays

After this line, values[3] becomes 6 ($3 + 3$)

```
public class Test {  
    public static void main(String[] args) {  
        int[] values = new int[5];  
        for (int i = 1; i < 5; i++) {  
            values[i] = i + values[i-1];  
        }  
        values[0] = values[1] + values[4];  
    }  
}
```

After the third iteration

0	0
1	1
2	3
3	6
4	0



Trace Program with Arrays

After this, i becomes 4

```
public class Test {  
    public static void main(String[] args) {  
        int[] values = new int[5];  
        for (int i = 1; i < 5; i++) {  
            values[i] = i + values[i-1];  
        }  
        values[0] = values[1] + values[4];  
    }  
}
```

After the third iteration

0	0
1	1
2	3
3	6
4	0



Trace Program with Arrays

i (=4) is still less than 5

```
public class Test {  
    public static void main(String[] args) {  
        int[] values = new int[5];  
        for (int i = 1; i < 5; i++) {  
            values[i] = i + values[i-1];  
        }  
        values[0] = values[1] + values[4];  
    }  
}
```

After the third iteration

0	0
1	1
2	3
3	6
4	0



Trace Program with Arrays

After this, values[4] becomes 10 ($4 + 6$)

```
public class Test {  
    public static void main(String[] args) {  
        int[] values = new int[5];  
        for (int i = 1; i < 5; i++) {  
            values[i] = i + values[i-1];  
        }  
        values[0] = values[1] + values[4];  
    }  
}
```

After the fourth iteration

0	0
1	1
2	3
3	6
4	10



Trace Program with Arrays

After $i++$, i becomes 5

```
public class Test {  
    public static void main(String[] args)  
    {  
        int[] values = new int[5];  
        for (int i = 1; i < 5; i++) {  
            values[i] = i + values[i-1];  
        }  
        values[0] = values[1] + values[4];  
    }  
}
```

After the fourth iteration

0	0
1	1
2	3
3	6
4	10



Trace Program with Arrays

i (=5) < 5 is false. Exit the loop

```
public class Test {  
    public static void main(String[] args) {  
        int[] values = new int[5];  
        for (int i = 1; i < 5; i++) {  
            values[i] = i + values[i-1];  
        }  
        values[0] = values[1] + values[4];  
    }  
}
```

After the fourth iteration

0	0
1	1
2	3
3	6
4	10



Trace Program with Arrays

After this line, values[0] is 11 ($1 + 10$)

```
public class Test {  
    public static void main(String[] args) {  
        int[] values = new int[5];  
        for (int i = 1; i < 5, i++) {  
            values[i] = i * values[i-1];  
        }  
        values[0] = values[1] + values[4];  
    }  
}
```

0	11
1	1
2	3
3	6
4	10