

# Data Types | Strings

# ■ String and &str

- ◆ Two commonly used types of strings
  - *String* – owned
  - *&str* – borrowed *String* slice
- ◆ Must use an owned *String* to store in a *struct*
- ◆ Use *&str* when passing to a function

## ■ Example – Pass to function

```
fn print_it(data: &str) {  
    println!("{}", data);  
}
```

```
fn main() {  
    print_it("a string slice");  
    let owned_string = "owned string".to_owned();  
    let another_owned = String::from("another");  
    print_it(&owned_string);  
    print_it(&another_owned);  
}
```

## ■ Example – Will not work

```
struct Employee {  
    name: &str,  
}  
  
fn main() {  
    let emp_name = "Jayson";  
    let emp = Employee {  
        name: emp_name  
    };  
}
```

# ■ Example – Works!

```
struct Employee {  
    name: String,  
}  
  
fn main() {  
    let emp_name = "Jayson".to_owned();  
    let emp_name = String::from("Jayson");  
    let emp = Employee {  
        name: emp_name  
    };  
}
```

# ■ Recap

- ◆ Strings are automatically borrowed
- ◆ Use `.to_owned()` or `String::from()` to create an owned copy of a string slice
- ◆ Use an owned `String` when storing in a struct