

# Developing Web Apps with Ruby on Rails

---

Prof. Paul Krause, University of Surrey  
Chapter 4, Lecture 1  
Using Active Record

# Objectives for today


---

- Remove our static Events page and replace it with an index page of dynamically generated Events
- This will introduce Rails' Active Record and its:
  - Object-Relation Mapping
  - Support for Database Migrations
  - Scaffold for generating everything you need to support an Events resource

# Object-Relational Mapping

---


- Classes map to Tables
- Attributes map to Columns in the respective Table
- Objects map to Rows
- Rails will handle the pluralisation automatically for you
  - (and usually gets it right)



# Object-Relational Mapping

---

- Classes map to Tables
- Attributes map to Columns in the respective Table
- Objects map to Rows
- Rails will handle the pluralisation automatically for you
  - (and usually gets it right)




People		

# Object-Relational Mapping

---

- Classes map to Tables
- Attributes map to Columns in the respective Table
- Objects map to Rows
- Rails will handle the pluralisation automatically for you
  - (and usually gets it right)




People		
ID	Name	DoB

# Object-Relational Mapping

---


- Classes map to Tables
- Attributes map to Columns in the respective Table
- Objects map to Rows
- Rails will handle the pluralisation automatically for you
  - (and usually gets it right)



People		
ID	Name	DoB
1	Paul	c1900

# The Event Model

---



# What do we want to do (with Events)?

---

- Create
  - a new Event
- Read
  - an existing Event
- Update
  - an existing Event
- Destroy
  - an existing Event



# How do we set up the database?

---

- Do nothing!
- Rails already has SQLite3 bundled and will generate the database for you

# The Prolog

---

- Start a new branch in your Git repository
- Strip out the:
  - Events action in the application controller
  - Events view
  - /events route in config/routes.rb

# Build a CRUD interface for the Event model

---

```
rails generate scaffold Event title:string date:date description:text
```

# Build a CRUD interface for the Event model

---

```
rails generate scaffold Event title:string date:date description:text
```



# Mapping Migration types to Database types

---

<b>Migration type</b>	<b>MySQL</b>	<b>SQLite</b>	<b>Ruby Class</b>
:binary	blob	blob	String
:boolean	tinyint(1)	boolean	Boolean
:date	date	date	Date
:datetime	datetime	datetime	Time
:decimal	decimal	decimal	BigDecimal
:float	float	float	Float
:integer	int(11)	integer	Fixnum
:string	varchar(255)	varchar(255)	String
:text	text	text	String
:time	time	time	Time
:timestamp	datetime	datetime	Time

# Run the database migration

---

```
rake db:migrate
```

# A set of routes for events in one statement

events\_controller.rb ✖

event.rb ✖


routes.rb ✖

```
1 AAAWebsite::Application.routes.draw do
2   resources :events
3
4   match "/index" => "aaa_core#index", via: :get
5   match "/shop" => "aaa_core#shop", via: :get
6   match "/discussion" => "aaa_core#discussion", via: :get
7   # The priority is based upon order of creation: first created -> highest priority.
8   # See how all your routes lay out with "rake routes".
9
10  # You can have the root of your site routed with "root"
11  root 'aaa_core#index'
12
```

# A little surprise!

---

- models/event.rb



```
events_controller.rb ✕ event.rb ✕
1 class Event < ActiveRecord::Base
2 end
3
```

- *Metaprogramming* enables Active Record to automatically add features to the model classes: e.g. it adds attributes to the model classes based on the columns in the corresponding database tables.



# White list for parameters from the scary Internet

In: app/controllers/events\_controller.rb

---

```
64 private
65 # Use callbacks to share common setup or constraints between actions.
66 def set_event
67   @event = Event.find(params[:id])
68 end
69
70 # Never trust parameters from the scary internet, only allow the white list through.
71 def event_params
72   params.require(:event).permit(:title, :date, :description)
73 end
```

# What we have done

---

- This has introduced Active Record
  - Probably the most impressive feature of Rails
- And we didn't even write one line of code!