ASHEVILLE, N CAR
ASHEVILLE REGL

GENERAL

Prior permission required for unscheduled air carrier operations with more than 30 passenger seats 0400-1200Z.

Low-level windshear alert system.

Birds on and in vicinity of airport.

Rwy 35 right traffic pattern.

Not for Navigational Purposes

ADDITIONAL RUNWAY INFORMATION									
ı						USABLE LENGTHS			
ı						-LANDING	⊢LANDINĢ BEYOND —		
RV	/Y					Threshold	Glide Slope	TAKE-OFF	WIDTH
17		HIRL	REIL	PAPI-L (angle 3.00°)	groove	0	5551'		100'
	35	● HIRL	REIL	PAPI-L (angle 3.00°)	grooved RV	₹	6017'		100
① Off when Twr inop; activate or increase intensity on 121.1.									
le u	2 LDA 6601'								

RUNWAY INCURSION HOT SPOTS HS1

HS1 _____

For information only, not to be construed as ATC instructions.

HS1 Maintain vigilance Twy A1 Hold Short lines Non-Standard.

HS2 Maintain vigilance Twy A4 Hold Short lines Non-Standard.

TAKE-OFF & OBSTACLE DEPARTURE PROCEDURE

		Rwy 17			Rwy 35			
		n climb of 1 to 4600'	For climb in Visual Conditions	With Mim climb of 410'/NM to 5700'		For climb in		
	Adequate Vis Ref	STD		Adequate Vis Ref	STD	Visual Conditions		
1 & 2 Eng	1/4	1	3600-3	RVR 16 or ¹ ∕ ₄	RVR 50 or 1	3600-3		
3 & 4 Eng		1/2			RVR 24 or $\frac{1}{2}$	3600-3		

OBSTACLE DP: Rwy 17; climb heading 167° to 4600' before proceeding on course.

Rwy 35; climb heading 347° to 5700' before proceeding on course.

VISUAL CLIMB OVER AIRPORT (VCOA): Rwys 17/35, obtain ATC approval for VCOA when requesting IFR clearance. Climb in visual conditions to cross Asheville Regl at or above 5600' MSL before proceeding on course.

Note: Visual Climb Over Airport not authorized at night.

TAKE-OFF OBSTACLE NOTES: Note Rwy 17, trees beginning 79' from DER, 452' right of centerline, up to 73' AGL/2144' MSL.

Note: Rwy 35, vehicle on road 44' from DER, 202' left of centerline, 15' AGL/2166' MSL. Trees beginning 65' from DER, 245' left of centerline, up to 92' AGL/2232' MSL. Trees beginning 701' from DER, 16' left of centerline, up to 65' AGL/2197' MSL.

L						
Γ	FOR FILING AS ALTERNATE					
l		Authorized Only When Twr Operating				
	RNAV (GPS) Rwy 17 RNAV (GPS) Rwy 35	ILS or LOC Rwy 35				
A B	H 800-2	1000-2	A			
	1200-3	1200-2	N			
	1500-3	1500-3	0			